

SR-455 / SR-485



DRIVE SAFETY

***your*safetyeyes**

THE MOST INTELLIGENT AND POWERFULL SUPER LIGHT STUD

SR-455

Unidirectional STUD

Technical Features

Rising from road surface: 8mm

Dimensions (visible surface): Ø160mm

Weight: 3Kg

Installation depth: 95mm

Material:

Main Body: Patented hard metallic stainless league, with hight mechanic and good corrosion resistance.

Base: Aluminum

Leds protection: 100% close polycarbonate box

LEDs: 8 Ultra Bright 5mm LEDs (white, blue, green, amber, red)

Power supply: [12/24V_{dc}], 80 mA

Communication protocol: RS485 (Optional)

Programable functions:

- Time ON / OFF - Flashing time - Always on mode - Brightness - Duty-Cycle

IP 68 Cable Protector

IP 68 Internal Connector for good replacement



SR-485

Bidirectional STUD

Technical Features

Rising from road surface: 8mm

Dimensions (visible surface): Ø160mm

Weight: 2,9Kg

Installation Depth: 95mm

Material:

Main Body: Patented hard metallic stainless league, with hight mechanic and good corrosion resistance.

Base: Aluminum

Leds Protection: 100% close polycarbonate box

LEDs: 16 Ultra Bright 5mm LEDs (white, blue, green, amber, red)

Power supply: [12/24V_{dc}], 160mA

Communication protocol: RS485 (Optional)

Programable functions:

- Time ON / OFF - Flashing time - Always on mode - Brightness - Duty-Cycle

IP 68 Cable Protector

IP 68 Internal Connector for good replacement



Advantages:

- Ideal for places subjected to frequent snow ploughing (Snowploughable)
- Very robust construction, adequated for very hard conditions
- High luminosity day or night
- Very easy replacement
 - Base (Fixed on the ground)
 - Main Body (Removable)
- PC remote Controlling (optional)
- Low maintenance
- Integration with 3rd party traffic control devices
- Auto Cleaning System
- Completely Water proof

→ Led's protection

→ Main Body

→ Base

Internal connection between **Main Body** and **Base** by a IP68 connector

100% Water-Proof!

Sysconnect

www.sysconnect.nl | +31 (0)10 2231307 | sales@sysconnect.nl